

## Compact magnetic cylinders - Series 32

Product code: 32M2A020A015

Datasheet creation date: 19/05/2026 08:57

Check the most updated document online [click here](#)



### TECHNICAL DATA

|                             |   |
|-----------------------------|---|
| <b>Series</b>               | 32  |
| <b>Version</b>              | M=male rod thread                                   |
| <b>Operation</b>            | 2=double-acting                                     |
| <b>Materials</b>            | A = anodized aluminium body, end blocks and piston, |
| <b>Diameter (mm)</b>        | 20  |
| <b>Construction</b>         | A = standard  |
| <b>Cylinder Stroke (mm)</b> | 15  |
| <b>Seal options</b>         | = standard  |
| <b>Rod length (mm)</b>      | 0   |
| <b>Rod length 2 (mm)</b>    | 0   |
| <b>Certifications</b>       | = standard  |

## Compact magnetic cylinders - Series 32

Product code: 32M2A020A015



### DIMENSIONS

|                 |      |
|-----------------|------|
| <b>A (mm)</b>   | 16   |
| <b>AF (mm)</b>  | 11   |
| <b>BG (mm)</b>  | 20.0 |
| <b>G (mm)</b>   | 10.9 |
| <b>Ø (mm)</b>   | 10   |
| <b>Ø (mm)</b>   | 9    |
| <b>D4 (mm)</b>  | 9    |
| <b>D5 (mm)</b>  | 6    |
| <b>D6 (mm)</b>  | 0    |
| <b>D7</b>       | M4   |
| <b>D8 (mm)</b>  | 4    |
| <b>E (mm)</b>   | 35.8 |
| <b>EE</b>       | M5   |
| <b>H (mm)</b>   | 8    |
| <b>KF</b>       | M6   |
| <b>KK</b>       | M8   |
| <b>LA (mm)</b>  | 5    |
| <b>L4 (mm)</b>  | 17   |
| <b>PL (mm)</b>  | 6.5  |
| <b>RT</b>       | M5   |
| <b>SW1 (mm)</b> | 8    |
| <b>T2 (mm)</b>  | 2    |
| <b>T3 (mm)</b>  | 0    |

|                |      |
|----------------|------|
| <b>TG (mm)</b> | 22.0 |
| <b>ZA (mm)</b> | 36.8 |
| <b>ZB (mm)</b> | 42.5 |
| <b>ZC (mm)</b> | 48.2 |