

## Cylinders ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 40K

Product code: 40K2L160A0050

Datasheet creation date: 20/05/2026 05:22

Check the most updated document online [click here](#)



### TECHNICAL DATA

Series ( mm)	40
Version ( )	K = standard, magnetic
Operation ( )	2 = double-acting (front and rear cushioning)
Materials ( )	L = rolled stainless steel rod AISI 420B anodized aluminium round tube NBR seals
Diameter ( mm)	160
Construction ( )	A = standard
Stroke ( mm)	50
Seal options ( )	= standard
Rod length ( mm)	0
Rod length 2 ( mm)	0
Protection options ( )	= standard
Certifications ( )	= standard

## Cylinders ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 40K

Product code: 40K2L160A0050



### DIMENSIONS

Ø ( mm)	40
KK ( )	M36x2
Ø D11 ( mm)	65
PL ( mm)	25.5
G ( mm)	15
L1 ( mm)	55
AM ( mm)	72
VA ( mm)	6
EE ( )	G3/4
WH ( mm)	80
L2 ( mm)	180
ZJ ( mm)	260
VD ( mm)	10
N ( mm)	50.0
RT ( )	M16
BG ( mm)	24
TG ( mm)	140
E ( mm)	180
SW1 ( mm)	36
SW3 ( mm)	4
SW4 ( mm)	55
Cushioning stroke ( mm)	33
XV1±2 ( mm)	145

XV2±2 ( mm)	170
XV3±2 ( mm)	195
h14 ( mm)	200
TK ( mm)	40
e9 ( mm)	32
h14 ( mm)	32
UW ( mm)	200
R ( mm)	0.2