

Cylinders ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 40K

Product code: 40K2L160A0150

Datasheet creation date: 20/05/2026 02:34

Check the most updated document online [click here](#)



TECHNICAL DATA

Series (mm)	40
Version ()	K = standard, magnetic
Operation ()	2 = double-acting (front and rear cushioning)
Materials ()	L = rolled stainless steel rod AISI 420B anodized aluminium round tube NBR seals
Diameter (mm)	160
Construction ()	A = standard
Stroke (mm)	150
Seal options ()	= standard
Rod length (mm)	0
Rod length 2 (mm)	0
Protection options ()	= standard
Certifications ()	= standard

Cylinders ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 40K

Product code: 40K2L160A0150



DIMENSIONS

Ø (mm)	40
KK ()	M36x2
Ø D11 (mm)	65
PL (mm)	25.5
G (mm)	15
L1 (mm)	55
AM (mm)	72
VA (mm)	6
EE ()	G3/4
WH (mm)	80
L2 (mm)	180
ZJ (mm)	260
VD (mm)	10
N (mm)	50.0
RT ()	M16
BG (mm)	24
TG (mm)	140
E (mm)	180
SW1 (mm)	36
SW3 (mm)	4
SW4 (mm)	55
Cushioning stroke (mm)	33
XV1±2 (mm)	145

XV2±2 (mm)	170
XV3±2 (mm)	195
h14 (mm)	200
TK (mm)	40
e9 (mm)	32
h14 (mm)	32
UW (mm)	200
R (mm)	0.2