

Cylinders ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 40K

Product code: 40K2L200A0050

Datasheet creation date: 20/05/2026 02:36

Check the most updated document online [click here](#)



TECHNICAL DATA

Series (mm)	40
Version ()	K = standard, magnetic
Operation ()	2 = double-acting (front and rear cushioning)
Materials ()	L = rolled stainless steel rod AISI 420B anodized aluminium round tube NBR seals
Diameter (mm)	200
Construction ()	A = standard
Stroke (mm)	50
Seal options ()	= standard
Rod length (mm)	0
Rod length 2 (mm)	0
Protection options ()	= standard
Certifications ()	= standard

Cylinders ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 40K

Product code: 40K2L200A0050



DIMENSIONS

Ø (mm)	40
KK ()	M36x2
Ø D11 (mm)	75
PL (mm)	25.5
G (mm)	15
L1 (mm)	65
AM (mm)	72
VA (mm)	8
EE ()	G3/4
WH (mm)	95
L2 (mm)	180
ZJ (mm)	275
VD (mm)	25
N (mm)	50.0
RT ()	M16
BG (mm)	24
TG (mm)	175
E (mm)	220
SW1 (mm)	36
SW3 (mm)	4
SW4 (mm)	55
Cushioning stroke (mm)	48
XV1±2 (mm)	160

XV2±2 (mm)	185
XV3±2 (mm)	210
h14 (mm)	250
TK (mm)	40
e9 (mm)	32
h14 (mm)	32
UW (mm)	250
R (mm)	0.2