

## Cylinders ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 40K

Product code: 40K2L200A0200

Datasheet creation date: 20/05/2026 04:33

Check the most updated document online [click here](#)



### TECHNICAL DATA

<b>Series ( mm)</b>	40
<b>Version ( )</b>	K = standard, magnetic
<b>Operation ( )</b>	2 = double-acting (front and rear cushioning)
<b>Materials ( )</b>	L = rolled stainless steel rod AISI 420B anodized aluminium round tube NBR seals
<b>Diameter ( mm)</b>	200
<b>Construction ( )</b>	A = standard
<b>Stroke ( mm)</b>	200
<b>Seal options ( )</b>	= standard
<b>Rod length ( mm)</b>	0
<b>Rod length 2 ( mm)</b>	0
<b>Protection options ( )</b>	= standard
<b>Certifications ( )</b>	= standard

## Cylinders ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 40K

Product code: 40K2L200A0200



### DIMENSIONS

Ø ( mm )	40
KK ( )	M36x2
Ø D11 ( mm )	75
PL ( mm )	25.5
G ( mm )	15
L1 ( mm )	65
AM ( mm )	72
VA ( mm )	8
EE ( )	G3/4
WH ( mm )	95
L2 ( mm )	180
ZJ ( mm )	275
VD ( mm )	25
N ( mm )	50.0
RT ( )	M16
BG ( mm )	24
TG ( mm )	175
E ( mm )	220
SW1 ( mm )	36
SW3 ( mm )	4
SW4 ( mm )	55
Cushioning stroke ( mm )	48
XV1±2 ( mm )	160

XV2±2 ( mm )	185
XV3±2 ( mm )	210
h14 ( mm )	250
TK ( mm )	40
e9 ( mm )	32
h14 ( mm )	32
UW ( mm )	250
R ( mm )	0.2