

## Cylinders ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 40K

Product code: 40K2L320A0300

Datasheet creation date: 20/05/2026 06:22

Check the most updated document online [click here](#)



### TECHNICAL DATA

<b>Series ( mm)</b>	40
<b>Version ( )</b>	K = standard, magnetic
<b>Operation ( )</b>	2 = double-acting (front and rear cushioning)
<b>Materials ( )</b>	L = rolled stainless steel rod AISI 420B anodized aluminium round tube NBR seals
<b>Diameter ( mm)</b>	320
<b>Construction ( )</b>	A = standard
<b>Stroke ( mm)</b>	300
<b>Seal options ( )</b>	= standard
<b>Rod length ( mm)</b>	0
<b>Rod length 2 ( mm)</b>	0
<b>Protection options ( )</b>	= standard
<b>Certifications ( )</b>	= standard

## Cylinders ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 40K

Product code: 40K2L320A0300



### DIMENSIONS

Ø ( mm )	63
KK ( )	M48x2
Ø D11 ( mm )	110
PL ( mm )	30.0
G ( mm )	35
L1 ( mm )	90
AM ( mm )	96
VA ( mm )	10
EE ( )	G1
WH ( mm )	120
L2 ( mm )	220
ZJ ( mm )	340
VD ( mm )	25
N ( mm )	65.0
RT ( )	M24
BG ( mm )	28
TG ( mm )	270
E ( mm )	350
SW1 ( mm )	55
SW3 ( mm )	6
SW4 ( mm )	75
Cushioning stroke ( mm )	50
XV1±2 ( mm )	210

XV2±2 ( mm )	230
XV3±2 ( mm )	250
h14 ( mm )	400
TK ( mm )	70
e9 ( mm )	50
h14 ( mm )	50
UW ( mm )	400
R ( mm )	0.0