

## Cylinders - aluminium profile ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 61

Product code: 61M2P100A0200

Datasheet creation date: 19/05/2026 08:43

Check the most updated document online [click here](#)




### TECHNICAL DATA

<b>Series</b>	61
<b>Diameter (mm)</b>	100
<b>Version</b>	M = magnetic standard
<b>Operation</b>	2=double acting (front and rear cushioning)
<b>Materials</b>	P = standard: AL end-blocks and piston, rolled stainless steel AISI 420B rod, anodized AL profile tube, zinc-plated steel tie-rods and tie-rod nuts, PU seals
<b>Construction</b>	A = standard with lock nut for rod
<b>Stroke type</b>	= standard
<b>Stroke (mm)</b>	200
<b>Seal options</b>	= standard
<b>Rod length (mm)</b>	0
<b>(mm)</b>	0
<b>Protection options</b>	= standard
<b>Certifications</b>	= standard

## Cylinders - aluminium profile ISO 15552 (ex DIN/ISO 6431 / VDMA 24562) - Series 61

Product code: 61M2P100A0200



### DIMENSIONS

MM (mm)	25
KK	M20x1,5
B d11 (mm)	55
PL (mm)	23
L1 (mm)	35
L11 (mm)	35
L12 (mm)	115
AM (mm)	40
VA (mm)	4
VAX (mm)	4
EE	G1/2
WH (mm)	51
L2 (mm)	138.0
ZM (mm)	-
ZJ (mm)	189
ZMX (mm)	240
ZJX (mm)	189
VD (mm)	7
N (mm)	38.5
BG (mm)	19.5
RT	M10
TG (mm)	89.0
G (mm)	8.0

R (mm)	40.0
E (mm)	110.0
SW1 (mm)	22
SW2 (mm)	10
SW3 (mm)	5
SW4 (mm)	30
Cushion stroke front spring	21
Cushion stroke rear spring	19
L3 (mm)	282.0
L4 (mm)	18
L5 (mm)	20
L6 (mm)	39.0
L7 (mm)	69.0
L8 (mm)	105
L9 (mm)	138.0
ø D (mm)	25
ø D1 d11 (mm)	55.0
ø D2 (mm)	100
ø D3 f6 (mm)	58
± 0.15 (mm)	89.0
GX	G1/8
H (mm)	58.0
H1 (mm)	110.5