

## Short stroke magnetic cylinders - Series QP-QPR

Product code: QP2A040A050

Datasheet creation date: 19/05/2026 08:35

Check the most updated document online [click here](#)



### TECHNICAL DATA

|                       |                            |
|-----------------------|----------------------------|
| <b>Series</b>         | QP = standard              |
| <b>Operation</b>      | 2=double-acting            |
| <b>Materials</b>      | A = rolled stainless steel |
| <b>Diameter (mm)</b>  | 40                         |
| <b>Construction</b>   | A = standard               |
| <b>Stroke (mm)</b>    | 50                         |
| <b>Seal options</b>   | -                          |
| <b>Certifications</b> | = standard                 |

## Short stroke magnetic cylinders - Series QP-QPR

Product code: QP2A040A050



### DIMENSIONS

|          |       |
|----------|-------|
| A (mm)   | 52.0  |
| B (mm)   | -     |
| B1 (mm)  | -     |
| B2 (mm)  | 40    |
| Ø C (mm) | 16    |
| D (mm)   | 57.00 |
| E (mm)   | 52.00 |
| G (mm)   | 42.4  |
| G1 (mm)  | 43.4  |
| H1 (mm)  | 10.7  |
| H (mm)   | 10.7  |
| J (mm)   | 5.5   |
| J1       | M8    |
| K (mm)   | 9.0   |
| L (mm)   | 6.0   |
| L1 (mm)  | 21.0  |
| M (mm)   | 13.5  |
| M1 (mm)  | 7.5   |
| N (mm)   | 47.9  |
| N1 (mm)  | -     |
| Ø O (mm) | 29.6  |
| P        | M8    |
| Q        | G1/8  |

|           |       |
|-----------|-------|
| R (mm)    | -     |
| R1 (mm)   | -     |
| R2 (mm)   | 40    |
| SW (mm)   | 13    |
| T (mm)    | 3.5   |
| U (mm)    | -     |
| V (mm)    | 31.00 |
| AA (mm)   | 10    |
| BB (mm)   | 6.0   |
| Ø CC (mm) | 9.0   |
| Ø DD (mm) | 5.5   |
| EE (mm)   | 9.0   |
| FF        | M5    |
| LL (mm)   | 40.0  |
| MM (mm)   | 52.0  |
| NN (mm)   | 50    |
| RR (mm)   | 40.0  |
| VV (mm)   | -     |
| Z (mm)    | 8.5   |